

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD ARTIKEL | INFORMATION UVP (CHF) | VI

WIRELESS PRO AUDIO
Transmitter
CORE


WiSpeak CORE is the transmitter device that communicates with all the receiver devices to create a WiSpeak wireless network, and takes the role of the Master Unit. Its main functions are to pair and send audio contents to all the receivers. Includes 3 audio inputs (Euroblock, RCA, Bluetooth), remote port for a WPa-VOL panel and a MUTE port for external dry contact triggering. Managed by WiSpeak grip app.

590.00
Receiver
TUBE3 (WH | BK)


WiSpeak TUBE is a self-powered 3" lamp style loudspeaker with wireless audio reception and control capabilities under the control of the Master unit, featuring an AUX output (Euroblock) and a installation system which is compatible with ceiling light rails.

490.00
CUBE5 (WH | BK)


WiSpeak CUBE is a self-powered 5" loudspeaker cabinet with wireless audio reception and control capabilities under the control of the Master unit, featuring an AUX output (Euroblock) and a installation system which is compatible with ceiling light rails. Alternatively, wall mount or desktop installation is as well possible by means of the included accessories.

590.00
GLOBE5RM (WH | BK)


WiSpeak GLOBE is a self-powered 2-way full range sphere loudspeaker cabinet with wireless audio reception and control capabilities under the control of a WiSpeak CORE Master unit, featuring an installation system which is compatible with ceiling light rails. Includes a 5" woofer and a 1" silk dome tweeter

550.00
GLOBE5PD (WH | BK)


WiSpeak GLOBE is a self-powered 2-way full range sphere loudspeaker cabinet with wireless audio reception and control capabilities under the control of a WiSpeak CORE Master unit, featuring a pendant installation system. Includes a 5" woofer and a 1" silk dome tweeter.

550.00
Accessories
TUBESMA (WH | BK)


TUBESMA is a surface mount adapter to allow installing a TUBE unit in locations where there is no available lighting rail.

50.00
SOUND SOURCES
Microphones
EMHH1


Affordable handheld cardioid dynamic microphone, with a robust design that makes it ideal for voice applications. It comes with a microphone stand adapter, 6 metres XLR-XLR cable and transport bag.



79.00
EMCN2


Condenser gooseneck cardioid microphone, with a perfect profile for message, speech and conferencing applications. Total length 55 cm. It includes anti-pop wind-screen cover.




145.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	<p>EMBASE Desktop connection base for the eMCN2 microphone, as well as for other microphones with standard XLR connector. It includes ON / OFF switch that enables / disables the microphone signal. Dimensions 45 x 140 x 110 mm. Weight: 860g.</p>	<p>110.00</p>
	<p>eMICFIT2 eMICFIT2 is a robust headset condenser microphone, including a water and sweat resistant treatment, ideal for sport and fitness applications. It performs an easy adjustment of the gooseneck and a discrete, light and comfortable design in combination with a robust and solid body. It features a mini-XLR 4-pin connector, compatible with the eMWE UHF wireless belt-pack unit. It includes anti-pop wind-screen cover and rigid case. Dimensions Ø 9.7 x 4.5mm / Ø 0.38" x 0.18". Weight 52 g / 0.11 lb.</p>	<p>160.00</p>

Audio Players

	<p>PLAYERONE Compact audio player with a stereo output that can play music contents from local storage media (USB/MicroSD card), Internet streams or digital sharing streams (DLNA and Airplay compatible). It includes Ethernet port, WiFi connection, USB and Micro-SD reader slots, front panel LCD display and local controls .Remote management by Ecler GALLERY, remote control by RePLAYER mobile app. Dimensions 241 x 44 x 152mm (install 2 PLAYER ONE in 1RU with 1UHRMKIT accessory). Weight 680 g.</p>	<p>590.00</p>
	<p>PLAYERZERO Compact audio player with a stereo output that can play music contents from local storage media (USB/MicroSD card), Internet streams or digital sharing streams (DLNA and Airplay compatible). It includes Ethernet port, WiFi connection, USB and Micro-SD reader slots .Remote management by Ecler GALLERY, remote control by RePLAYER mobile app. Dimensions 126.5 x 44 x 132 mm / 4.98" x 1.73" x 5.19". Weight 0.6 Kg / 1.32 lb</p>	<p>470.00</p>
	<p>DUONETPLAYER Double audio sound source that features full EclerNet compatibility (UCP control system, WPNETTOUCH remote management, TP-NET protocol, etc.). It includes 2 independent stereo media players, each one being able to play Internet audio streams and local (USB/SD) or networked audio media. The device have 2 Euroblock line level balanced outputs, remote control, priority (messages, warnings) and 4 GPI ports to trigger events. Dimensions 482 x 44(1RU) x 250mm. Weight 4,2 kg</p>	<p>1'290.00</p>
	<p>ESASBT Stereo audio source including FM tuner, USB slot, SD slot and Bluetooth connection. It performs unbalanced and balanced stereo audio outputs and headphones output (jack) with volume control in frontal panel. IR remote control, FM antenna, 2x RCA cables and rack-mount bracket included. Dimensions 482 x 44(1RU) x 132mm. Weight 1,4 kg</p>	<p>290.00</p>

INSTALLATION MIXERS
SAM Series

ESAM402

Installation audio mixer in standard rack format, featuring 3 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom power for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,7 kg

390.00

ESAM702

Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom available for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,8 kg

590.00

ESAM603

6 inputs and 3 outputs installation audio mixer. Inputs: 1x MIC, 4x MIC/LINE ST, 1x LINE ST. Outputs: 1x ST (A/B) and 1x MONO (C). A/B output can operate in ST/MONO mode. Each input can be routed to output A, B and/or C. It includes a 3 band tone control section, talkover (priority) function assignable to each input over the mix bus, ST/MONO mix switch for A/B output and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,1 kg

590.00

SAM412T

Ecler SAM412T is an installation mixer in standard rack format. It includes 4 MIC / ST LINE inputs, 2 outputs (1 balanced stereo, 1 stereo) and 1 REC output, independent 3 band tone control per each input, Talkover (priority) function and external MUTE connection port. Dimensions 482.6x44(1RU)x195 mm. Weight 2,4 kg

590.00

SAM612T

Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs + 1 ST MIX input and 1 stereo balanced output. Each input has a dedicated 3-band tone control and 18V phantom power for MIC inputs. Input 1 includes talkover (priority) function over the mix bus and additional front panel jack connector. Main output ST/MONO mode switch and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,0 kg

690.00
COMPACT Series
ECOMPACT4BT


Desktop/19" rack installation mixer. INS: 4 mic with switchable HP-filter and Phantom power 48V; 6 line ST; Bluetooth® connex; aux (mini-jack). OUTS: main balanced (XLR) with ST/mono switch; SUB OUT mono (XLR) with switchable LP-filter; alternative ALT (RCA); headphones (mini-Jack). 3 Band tone Ctrl and ALT OUT (alternative output) send per channel on all channels; Talkover (CH4) with mic input (combo) and USB charging port. It includes power supply and rack-mount kit.

850.00

SAMI Series



SAMI402

Installation audio mixer in standard rack format, featuring 3 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom power for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1.7 ka

TBC Q3



SAMI702BT

Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs, 1 BT input, 1 main mix balanced output and one AUX/REC additional output. It includes a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, 18V phantom available for all mic inputs, ST/MONO mix switch and MUTE port for external dry contact triggering. Dimensions 482.6 x 44(1RU) x 120 mm. Weight 1,8 kg

TBC Q3



SAMI603

6 inputs and 3 outputs installation audio mixer. Inputs: 1x MIC, 4x MIC/LINE ST, 1x LINE ST. Outputs: 1x ST (A/B) and 1x MONO (C). A/B output can operate in ST/MONO mode. Each input can be routed to output A, B and/or C. It includes a 3 band tone control section, talkover (priority) function assignable to each input over the mix bus, ST/MONO mix switch for A/B output and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2,1 kg

TBC Q3



SAMI612

Installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs + 1 ST MIX input and 1 stereo balanced output. Each input has a dedicated 3-band tone control and 18V phantom power for MIC inputs. Input 1 includes talkover (priority) function over the mix bus and additional front panel jack connector. Main output ST/MONO mode switch and MUTE port for external dry contact triggering. Dimensions 482.6x44(1RU)x120 mm. Weight 2.0 ka

TBC Q3

DIGITAL MATRIXES & PROCESSORS

Digital Zonemixer



DAM614

Fully programmable audio digital mixer. It includes 6 audio inputs (2x LINE ST + 4x LINE/MIC being possible to use them independently (mono) or as stereo-coupled inputs) and 4 audio outputs (can be used as mono or stereo zones). Phantom power, front panel inputs and outputs level controls, DSP processing, RS-232 connectivity (compatible with EclerCOMM/CA-NET) and 4 REMOTE control ports (0-10VDC). Dimensions 482.6 x 44(1RU) x 120 mm. Weight 2.00 ka

1'150.00

Digital Matrixes | MIMO Series
MIMO7272DN


64x64 native processing digital matrix with 72 inputs and 72 outputs (8 analogue inputs, 8 analogue outputs, 64 Dante™ inputs and 64 Dante™ outputs). Incorporating audio over IP technology, MIMO7272DN allows signal transmission using a Local Ethernet network. It features accessories from WPNET Series connected by Ethernet. MIMO7272DN is also capable of executing EclerNet projects thanks to its processor acting as a UCP server. Dimensions 482,6x44x266,5mm. Weight 3.25 kg

4'490.00
MIMO4040CDN


Digital matrix with native processing of 40 inputs and 40 outputs (8 analogue inputs, 8 analogue outputs, 32 Dante™ inputs and 32 Dante™ outputs). MIMO4040CDN comes with a CONFERENCE tailored firmware, including Automixer, Feedback Killer and Acoustic Echo Cancelling functions. It features accessories from WPNET Series connected by Ethernet. MIMO4040CDN is also capable of executing EclerNet projects thanks to its processor acting as a UCP server. Dimensions 482,6x44x266,5mm. Weight 3.25 kg

4'490.00
M40AEC2EXP

Expansion license +2 AEC processing channels for MIMO4040CDN

140.00

*up to 8 AEC channels max. available in MIMO4040CDN

M40AEC4EXP

Expansion license +4 AEC processing channels for MIMO4040CDN

280.00

*up to 8 AEC channels max. available in MIMO4040CDN

M40AEC6EXP

Expansion license +6 AEC processing channels for MIMO4040CDN

420.00

*up to 8 AEC channels max. available in MIMO4040CDN


MIMO88


8 balanced MIC/LINE inputs / 8 balanced outputs + 2 monitor outputs digital audio matrix, fully programmable through EclerNet Manager and linkable to a second unit to become a 16x16 matrix. Includes 8 GPI and 8 GPO ports. DSP processing: Parametric EQ & filters for each channel, delays, compressor/limiter, paging, priority, automatic mix (MIMO Firmware) and remote control via UCP or WPNETTOUCH. Dimensions 482.6 x 44 x 266.5 mm. Weight 3.5 kg


3'380.00
MIMO88SG



8 balanced MIC/LINE inputs / 8 balanced outputs digital audio matrix, fully programmable through EclerNet Manager. Includes 8 GPI ports. DSP processing: Parametric EQ & filters for each channel, delays, compressor/limiter, paging, priority, automatic mix (MIMO Firmware) and remote control via UCP or WPNETTOUCH. Dimensions 482.6 x 44 x 266.5 mm. Weight 3.5 kg

1'990.00


BILD	ARTIKEL INFORMATION	
	<p>MIMO1212SG</p> <p>12 balanced MIC/LINE inputs / 12 balanced outputs digital audio matrix, fully programmable through EclerNet Manager. Includes 12 GPI ports. DSP processing: Parametric EQ & filters for each channel, delays, compressor/limiter, paging, priority, automatic mix (MIMO Firmware) and remote control via UCP or WPNETTOUCH. Dimensions 1RU x 266,5mm depth. Weight 3,5 kg</p>	<p>2'390.00</p>

Digital Zoners | HUB Series


	<p>HUB1408</p> <p>HUB1408 is a digital audio zoner with a global size of 14 input and 8 output analogue channels. Available inputs are 4 MIC/LINE and 2 ST LINE local inputs, and 8 REMOTE LINE inputs. Available DSP: frequency shifter, link stereo, delay, crossover filters, graphic EQ, compressor/limiter and much more. Ecler pilot application, compatible with Android and iOS: control graphic panels set to user requirements. HxWxD: 88 (2RU) x 482,6 x 200mm. Weight 3,7 kg</p>	<p>1'490.00</p>
--	---	------------------------


	<p>HUB1616</p> <p>HUB1616 is a digital audio zoner with a global size of 16 input and 16 output analogue channels. The input channels are: 4 channels for MIC/MONO LINE, 4 channels for ST LINE and 8 channels for MONO LINE received on the unit's REMOTE ports, from wall panels eMCONTROL1. Available DSP: frequency shifter, link stereo, delay, crossover filters, graphic EQ, compressor/limiter and much more. Ecler pilot application, compatible with Android and iOS: control graphic panels set to user requirements. HxWxD: 88 (2RU) x 482,6 x 200mm. Weight 3,7 kg</p>	<p>1'990.00</p>
---	--	------------------------

DANTE Interfaces

	<p>DN44BOB</p> <p>4 inputs/4 outputs DANTE (Audio Over IP) Break Out Box. It allows to convert 4 analogue audio signals into 4 DANTE channels and send them into an Ethernet LAN, as well as to take 4 DANTE channels from the Ethernet network and convert them to analogue audio signals. It includes 4 GPI (0-10VDC) and 4 GPO control ports (NO/NC relays). Can be used together with EclerNet DANTE ready products or as a stand-alone DANTE interface. PUM3 included: rack-mount accessory to mount 2 halfwidth RU devices in 1 standard width RU space. Dimensions 241 x 44(1RU) x 152 mm. Weight 1.1 kg</p>	<p>1'290.00</p>
--	--	------------------------

Loudspeakers Processors | ALMA Series

	<p>ALMA24</p> <p>Digital loudspeaker manager including 2 audio inputs and 4 audio outputs (all balanced), USB interface and 2 volume remote control ports (0-10VDC). Includes DSP processor 24bits/48kHz, parametric EQ, 3 crossover types, 20 user presets and password protection. ALMA24 is a 1RU stand-alone processor and EclerCOMM Manager compatibility. Dimensions 482.6 x 44 x 120 mm. Weight 1.75 kg</p>	<p>790.00</p>
--	---	----------------------

	<p>ALMA26</p> <p>Digital loudspeaker manager including 2 audio inputs and 6 audio outputs (all balanced), USB interface and 2 volume remote control ports (0-10VDC). Includes DSP processor 24bits/48kHz, parametric EQ, 3 crossover types, 20 user presets and password protection. ALMA24 is a 1RU stand-alone processor and EclerCOMM Manager compatibility. Dimensions 482.6 x 44 x 120 mm. Peso 1.75 kg</p>	<p>1'050.00</p>
--	---	------------------------

AMPLIFIERS
Networkable Amplifiers | VIDA Series

NEW PRODUCT


VIDA16Q

1600W digital amplifier, with 4 amplified outputs that can be independently configured in high (100/70V) or low (8/4/2ohm) impedance. The VersaPower technology, developed by Ecler, allows an asymmetrical power distribution. Max output power @ 2Ω/4Ω/8Ω or @70/100V - Single channel is 400W. Audio player - with microSD slot for local audio files - as well as signal generator, plus 2 auxiliary line outputs and 4 Dante digital outputs. Internal matrix and signal processing. Remote control user application for iOS/Android/Web. Control and scheduled events for automation. Ultra low power consumption mode. Dimensions 482,6x88(2RU)x410 mm / 19"x3.46"x16.14". Weight 9,3 kg. / 20.5 lb.

2'890.00

NEW PRODUCT


VIDA24Q

2400W digital amplifier, with 4 amplified outputs that can be independently configured in high (100/70V) or low (8/4/2ohm) impedance. The VersaPower technology, developed by Ecler, allows an asymmetrical power distribution. Max output power @ 2Ω/4Ω/8Ω or @70/100V - Single channel is 600W. Audio player - with microSD slot for local audio files - as well as signal generator, plus 2 auxiliary line outputs and 4 Dante digital outputs. Internal matrix and signal processing. Remote control user application for iOS/Android/Web. Control and scheduled events for automation. Ultra low power consumption mode. Dimensions 482,6x88(2RU)x410 mm / 19"x3.46"x16.14". Weight 9,3 kg. / 20.5 lb.

3'490.00

NEW PRODUCT


VIDA48Q

4800W digital amplifier, with 4 amplified outputs that can be independently configured in high (100/70V) or low (8/4/2ohm) impedance. The VersaPower technology, developed by Ecler, allows an asymmetrical power distribution. Max output power @ 2Ω/4Ω/8Ω or @70/100V - Single channel is 1200W. Audio player - with microSD slot for local audio files - as well as signal generator, plus 2 auxiliary line outputs and 4 Dante digital outputs. Internal matrix and signal processing. Remote control user application for iOS/Android/Web. Control and scheduled events for automation. Ultra low power consumption mode. Dimensions 482,6x88(2RU)x410 mm / 19"x3.46"x16.14". Weight 9,3 kg. / 20.5 lb.

3'990.00 Q2
Networkable Amplifiers | HADA Series

NEW PRODUCT


HADA-4B150

HADA-4B150 is a 4x125W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 4.7 Kg / 10.36 lbs

1'450.00 Q2

NEW PRODUCT


HADA-4B250

HADA-4B250 is a 4x250W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 5.0 Kg / 11.02 lb

1'560.00 Q2

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

UVP (CHF) | VI

BILD	ARTIKEL INFORMATION		
	HADA-4B400 HADA-4B400 is a 4x400W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 5.4 Kg / 11.91 lb	1'700.00	Q2
	HADA-4B500 HADA-4B500 is a 4x500W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. 5.6 Kq / 12.35 lb	1'820.00	Q2
	HADA-4B750 HADA-4B750 is a 4x750W digital amplifier that supports low and high impedance loads. The internal DSP, through the HADA DSP Manager software, allows tailoring the input and output signal through parametric EQs, multi-band compressors, limiters, and delays and each configuration can be saved as a preset.. Dimensions 482.6 x 88 x 281,5 mm / 19 x 3.46 x 11.08 in. Weight 6.0 Kg / 13.22 lb	2'250.00	Q2

Networkable Amplifiers | NXA Series

	NXA 4-80 4 in /4 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (4 x 85W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 4 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88 x 373 mm. Weight 9.2 ka	1'890.00	EOL
	NXA 4-200 4 in /4 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (4 x 202W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 4 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 12.6 ka	2'590.00	EOL
	NXA 4-400 4 in /4 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (4 x 416W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 4 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 16.0 ka	3'790.00	EOL
	NXA 6-80 6 in /6 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier(6 x 84W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 6 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 10.2 ka	2'290.00	EOL

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD

ARTIKEL | INFORMATION

UVP (CHF) | VI


NXA 6-200

6 in /6 out self-powered digital manager that stays halfway between a digital matrix and a class D multichannel amplifier (6 x 218W @ 4Ω RMS). Includes a powerful DSP processor, auto stand-by function, convection cooling, health self-test mode function and 6 GPI ports. Compatible with EclerNet Manager platform and UCP remote control system. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 14.1 kg

2'990.00 EOL
Commercial Amplifiers | AURA Series

AURA-2H150

Stereo amplifier with 2 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its adjustable auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 221mm. Weight 6.05 kg

TBC Q3


AURA-4H150

Multichannel amplifier with 4 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 341mm. Weight 10.5 kg

TBC Q3

AURA-2L150

Stereo, 2x150 WRMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function, fanless design 100% silent.. Dimensions 440 x 44(1RU) x 161 mm. Weight 2.60 kg


TBC Q3

AURA-4L150

4x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. Dimensions 482.6 x 44(1RU) x 221 mm. Weight 3.60 kg


TBC Q3

AURA-8L150

8x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. Dimensions 482.6 x 44(1RU) x 341 mm. Weight 6 kg

TBC Q3
Commercial Amplifiers | eLPA Series

ELPA2-350

Stereo amplifier delivering 2 x 345 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Built in crossover (150Hz), permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 560 WRMS. Dimensions 482.6 x 88(2RU) x 266 mm. Weight 5.50 kg

790.00

ELPA2-650


Stereo amplifier delivering 2 x 630 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 1220 WRMS. Dimensions 482.6 x 88(2RU) x 266 mm / 6.00kg

970.00


ELPA2-950


Stereo amplifier delivering 2 x 950 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 1840 WRMS. Dimensions 482,6 x 88(2RU)x 266 mm. Weight 6,15 kg


1'190.00


BILD	ARTIKEL INFORMATION	
	<p>ELPA2-1400 Stereo amplifier delivering 2 x 1400 WRMS @ 4Ω. Have 2 XLR balanced inputs, 2 Speakon® and terminal type connection outputs. Ultra light and versatile format. Permanently activated anti-clip circuit and efficient progressive ventilation system. 2 Bridged Channels @ 8 Ω 2600 WRMS. Dimensions 482,6 x 88(2RU) x 304 mm. Weight 6,35 kg</p>	1'290.00

Commercial Amplifiers | eGPA Series


	<p>EGPA2-150 Stereo, 2x150 WRMS @ 4 Ω, high efficiency amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 280 WRMS. Dimensions 440 x 44(1RU) x 161 mm. Weight 2.60 kg</p>	650.00
--	--	---------------


	<p>EGPA2-300 Stereo, 2x310 WRMS @ 4 Ω, high efficiency stereo amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 600 WRMS. Dimensions 440 x 44(1RU) x 221 mm. Weight 3.40 kg</p>	860.00
--	---	---------------

	<p>EGPA4-150 4x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 280 WRMS. Dimensions 482.6 x 44(1RU) x 221 mm. Weight 3.60 kg</p>	960.00
--	---	---------------


	<p>EGPA8-150 8x150 WRMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function, fanless design 100% silent. 2 Bridged Channels @ 8Ω 280 WRMS. Dimensions 482.6 x 44(1RU) x 341 mm. Weight 6 kg</p>	1'850.00
--	--	-----------------

Commercial Amplifiers | GPA Series

	<p>GPA2-400ES Stereo amplifier delivering 2 x 350 WRMS @ 4 Ω. True green profile: high efficiency, auto stand-by function, 100% silent fanless design, Energy Star certified. 2 remote volume control ports and bridge mode 2 channels @ 8Ω 700 WRMS. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 10.8 kg</p>	1'190.00
--	--	-----------------

	<p>GPA2-800 Stereo amplifier delivering 2 x 720 WRMS @ 4 Ω, and ready to drive 1000 WRMS @ 2Ω loudspeaker loads (4 x 8 Ω loudspeakers in parallel, per channel). True green profile: high efficiency, auto stand-by function, 100% silent fanless design. 2 remote volume control ports and bridge mode 2 Channels @ 8Ω 1150 WRMS. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 10.8 kg</p>	1'590.00
--	---	-----------------

Commercial Amplifiers | HZA Series

	<p>HZA4-120F 4 x MERGING channel amplifier with direct 4 x 120 WRMS @ 100 V line (high impedance) outputs. Every 2, 3 or 4 adjacent channels can be merged, adding their output power and managing as a single merged channel: 1x 120 WRMS, 2x 200 WRMS, 3x 290 WRMS, 4x 360 WRMS. High efficiency and improved low-end frequency response. Includes 4 remote volume control ports, auto stand-by function and convection cooling 100% silent. Dimensions 482.6 x 88(2RU) x 392 mm. Weight 13.60 kg</p>	1'590.00
--	--	-----------------

Commercial Amplifiers | eHSA Series

EHSA2-150

Stereo amplifier with 2 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 221mm. Weight 6.05 kg

890.00

EHSA2-500

Stereo amplifier with 2 x 500 WRMS @ 100V (high impedance) powered outputs. Includes 2 mono balanced inputs (Euroblock terminals) with stack outputs. Dispose of selectable HPF, thermal and overload protection, anti-clip system, and volume control trimmers on rear panel. Dimensions 482.6 x 88(2RU) x 365mm. Weight 6.3kg

1'390.00

EHSA4-60

Multichannel amplifier Class D with 4x60 WRMS @ 70/100V (high impedance) powered outputs, and low impedance output. Its noiseless convection cooling, and its auto stand-by function provide this amplifier with a true green profile. Include link channel buttons, that allows to replicate the input channel signal in the adjacent one. Dimensions 482,6 x 44(1RU) x 280mm. Weight 7,8 kg

950.00

EHSA4-150

Multichannel amplifier with 4 x 150 WRMS @ 70/100V (high impedance) powered outputs. Its noiseless convection cooling, a very high efficiency and its auto stand-by function provide this amplifier with a true green profile. Dimensions 440 x 44(1RU) x 341mm. Weight 10.5 kg

1'290.00

EHSA4-500

Multichannel amplifier with 4 x 500 WRMS @ 100V (high impedance) powered outputs. Includes 2 mono balanced inputs (Euroblock terminals) with stack outputs. Dispose of selectable HPF, thermal and overload protection, anti-clip system, and volume control trimmers on rear panel. Dimensions 482.6 x 88(2RU) x 365mm. Weight 7.6 kg

1'990.00

HSA2-400ES

Stereo amplifier with low and high impedance powered outputs (2x400 WRMS). Includes 2 balanced inputs (XLR and Euroblock), 2 remote volume ports and Euroblock outputs. True green profile(Energy Star® Certification): auto stand-by function and noiseless convection cooling. Dimensions 482.6 x 88(2RU) x 373 mm. Weight 16.4 kg

1'490.00
Mixing Amplifiers | eHMA Series

EHMA60

Self-powered audio mixer including 1 MIC input and two MIC/LINE ST inputs. It features a 60W powered output that supports both low (4 Ω) and high impedance (70/100V) loudspeaker lines. It also includes an audio priority system, phantom power, 2 band tone control, auto stand-by mode, MUTE port and universal power supply unit (24 VDC IN).Dimensions 200x44x150 mm. Weight 1.9kg. 1UHRMKIT Rack Mount Kit included.

490.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD

ARTIKEL | INFORMATION

UVP (CHF) | VI


EHMA120

Stereo, Self-powered audio mixer including 3x MIC/LINE ST and 1x LINE ST input. It features a 95W powered mono output that supports both low (4Ω) and high impedance (70/100V) loudspeaker lines, with 2-ZONE ON/OFF switches. Includes audio priority system, pager (1 zone), phantom, 2 band tone control, auto stand-by, MUTE port and universal power supply unit (compatible with 24 VDC IN). Dimensions 435x44x120 mm. Weight 2.9kg 1UHRMKIT Rack Mount Kit included

690.00

EHMA250

Self-powered audio mixer including 2 MIC, 2 MIC/LINE ST and 2 LINE ST inputs. It features a 250W powered mono output that supports both low (4 and 8Ω) and high impedance (50/70/100V) loudspeaker lines, with 4-ZONE ON/OFF switches. Includes an audio priority system, Pager (1 zone), phantom power, remote control port (WpM), AUX/REC output, 2 band tone control, auto stand-by mode and MUTE port. Dimensions 435x220x44mm / 17,1"x8,7"x1,7"mm. Weight 3kg / 6.6lb.

1'050.00
Mixing Amplifiers | HMA Series

HMA120

Self-powered mixer including an integrated media player (USB,SD) and 5 external audio inputs: 3 x LINE ST, 1 MIC/LINE and 1 MIC. It features a 120W powered output that supports both low (4Ω) and high impedance (70/100V) loudspeaker lines. It also includes a 2 level priority system, auto stand-by mode, 2 band control tone, AUX OUT and a remote control port WpM series compatible. Dimensions 210 x 88 x 230 mm. Weight 5.95 kg Compatible with the 2UHRMKIT Rack Mount Kit.

790.00
Ultra Compact Amplifiers | CA Series

CA40

2 x 20 WRMS @ 4Ω stereo compact amplifier with a balanced MIC input (includes phantom power, Talkover and noise gate) and 2 LINE inputs. 3 output modes (STEREO, PARALLEL and BRIDGE) and AUX output. 2 band control tone, IR remote control included, serial RS-232 port (EclerCOMM and CA-NET compatible) and 0-10 VDC remote port for WpM wall panel series (volume and source selection). Auto-standby function and MUTE port. Dimensions 155 x 155 x 45 mm. Weight 0.65 kg

420.00

CA120

2 x 60 WRMS @ 4Ω stereo compact amplifier with a MIC/LINE input (includes phantom power, Talkover and noise gate) and 2 LINE inputs. AUX output. Control features: 2 band control tone, IR remote control included, serial RS-232 port (EclerCOMM and CA-NET compatible) and 0-10 VDC remote port for WpM wall panel series (volume and source selection). Auto-standby function and MUTE port. Dimensions 160 x 210 x 48 mm. Weight 0.95 kg

590.00

CA120HZ

High impedance version of the CA120, delivering 120W @ 70/100V line level, with a MIC/LINE input (includes phantom power, Talkover and noise gate) and 2 LINE inputs. AUX output. Control features: 2 band control tone, IR remote control included, serial RS-232 port (EclerCOMM and CA-NET compatible) and 0-10 VDC remote port for WpM wall panel series (volume and source selection). Auto-standby function and MUTE port. Dimensions 160 x 325 x 48 mm. Weight 2.92 kg

650.00

Ultra Compact Amplifiers | eCA Series

ECA120

2 x 60 WRMS @ 4 Ω stereo micro-amplifier, in a very compact format and a light and silent (fanless) design. It features 1 LINE ST input (RCA/Euroblock), AUTO STANDBY function and volume remote control, compatible with Ecler WPmVOL and WPmVOL-SR wall panels (0-10 VDC). Auto-standby function. External, universal and CE/UL/CCC certified power supply. Dimensions: 190 x 48 x 90mm. Weight 600 g.

490.00

ECA120HZ

2 x 60 WRMS @ 4 Ω stereo micro-amplifier, in a very compact format and a light and silent (fanless) design. It features 1 LINE ST input (RCA/Euroblock), AUTO STANDBY function and volume remote control, compatible with Ecler WPmVOL and WPmVOL-SR wall panels (0-10 VDC). Auto-standby function. External, universal and CE/UL/CCC certified power supply. Dimensions: 190 x 48 x 90mm. Weight 600 g.

550.00
LOUDSPEAKERS
In-Ceiling Loudspeakers

IW103

3" in-ceiling / in-wall installation loudspeaker featuring a rectangular and discreet design, and including a high impedance transformer unit with 15 and 30 W power selections @ 100V line level. Dimensions 110 x 165 x 80 mm. Weight 900g. Delivered by master carton of 8 units. Price per unit.

90.00
In-Ceiling Loudspeakers | eIC Series

EIC51FM

Fast installation in-ceiling loudspeaker. It features a 4,5" woofer, 6 WRMS @ 8 Ω nominal power and 70/100V line transformer with 3 and 6 W power selections. Internal diameter 150 mm. External diameter 160mm. Required depth 54mm. Weight 500g. Price per unit.

27.00

EIC52

2-way cost-effective in-ceiling loudspeaker with a great sound performance. It features a 5,25" woofer and a 0,75" tweeter, 20 WRMS @ 8 Ω nominal power and 100V line transformer with 3 and 6 W power selections. Internal diameter 164mm. External diameter 202mm. Required depth: 65mm. Weight 1.0 kg Delivered by master carton of 8 units. Price per unit.

60.00

EIC52MS

2-way in-ceiling loudspeaker suitable for installations exposed to extreme humidity and/or temperature. It features 1x5" woofer and 1x1" tweeter with a global power admission of 20 WRMS @ 8Ω. Internal diameter 120mm. External diameter 165mm. Required depth 79mm. Weight 700g. Delivered by units. Price per unit.

75.00
In-Ceiling Loudspeakers | VIC Series

VIC6

2-way loudspeaker is the perfect option for 70/100 V (2,5/5/10/20/40 W) and low impedance sound solutions (40 WRMS @8Ω). It mounts a 6,5" woofer and a 0,5" steerable tweeter in a discreet design. Dimensions (ØxD): 232x105mm. Weight 1,8kg. Delivered by master carton of 2 units. Price per unit.

130.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	<p>VIC6X 2-way loudspeaker is the perfect option for 70/100 V (2,5/5/10/20/40 W) and low impedance sound solutions (40 WRMS @8Ω). It mounts a 6,5" woofer and a 0,5" steerable tweeter in a discreet design. With plastic back can and tile bridge. Dimensions (ØxD): 232x170mm. Weight 1,8kg. Delivered by master carton of 2 units. Price per unit.</p>	190.00
	<p>VIC8 2-way loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions (60 WRMS @8Ω). It mounts an 8" woofer and a 0,5" steerable tweeter in a discreet design. Dimensions (ØxD): 282x115mm. Weight 2,3kg. Delivered by master carton of 2 units. Price per unit.</p>	170.00
	<p>VIC8X 2-way loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions (60 WRMS @8Ω). It mounts an 8" woofer and a 0,5" steerable tweeter in a discreet design. With plastic back can and tile bridge. Dimensions (ØxD): 282x200mm. Weight 3,1kg. Delivered by master carton of 2 units. Price per unit.</p>	290.00
	<p>VICSB8 Sub-woofer reinforcement loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions. It mounts an 8" providing 80 WRMS power in a discreet design. Dimensions (ØxD): 282x135mm. Weight 3,1kg.</p>	290.00
	<p>VICSB8X Sub-woofer reinforcement loudspeaker is the perfect option for 70/100 V (3,75/7,5/15/30/60 W) and low impedance sound solutions. It mounts an 8" providing 80 WRMS power in a discreet design. With plastic back can and tile bridge. Dimensions (ØxD): 282x200mm. Weight 3,9kg</p>	390.00

In-Ceiling Loudspeakers | IC Series

	<p>IC3 (WH BK) 1-way loudspeaker is the perfect option for 70/100 V (0.75/1.5/3/6 W) and low impedance sound solutions. It mounts a 3" woofer in a discreet design. Cutout size 90mm. Internal diameter 88mm. External diameter 105mm. Required depth 90mm. Weight 500g. White or black colour. Delivered by master carton of 2 units. Price per unit.</p>	70.00
	<p>IC6 (WH BK) 1-way loudspeaker is the perfect option for 70/100 V (0.75/1.5/3/6 W) and low impedance sound solutions. It mounts a 3" woofer in a discreet design. Cutout size 90mm. Internal diameter 88mm. External diameter 105mm. Required depth 90mm. Weight 500g. White or black colour. Delivered by master carton of 2 units. Price per unit.</p>	100.00
	<p>IC8 2-way loudspeaker is the perfect option for 70/100 V (5/7.5/15/30 W) and low impedance sound solutions (60 WRMS @8Ω). It mounts an 8" woofer and a 1" tweeter in a discreet design. Cutout size 222mm. Internal diameter 220mm. External diameter 245mm. Required depth 91mm. Weight 2,3kg. Delivered by master carton of 2 units. Price per unit.</p>	290.00

High Performance Loudspeakers | MIA Series



MIA-81 (WH | BK)

MIA-81 is a an elegant, unique a compact design column loudspeaker, built in a single aluminium piece to avoid vibrations and mechanical stress. MIA-81 includes 8x1.5" drivers delivering 40WRMS and the possibility of working in 16 Ω or 64 Ω. IP44 rated. Includes a versatile smart pan and tilt bracket made out of stainless-steel that permits adjusting the height at any point of the length of the column. White or black colour. Dimensions 58 x 448 x 67 mm / 2.28 x 17.64 x 2.64 in. (WxHxD). Weight 1.2 kg / 1.64 lb. Delivered by units. Price per unit.

680.00 Q2




MIA-82 (WH | BK)

MIA-82 is a an elegant, unique a compact design column loudspeaker, built in a single aluminium piece to avoid vibrations and mechanical stress. MIA-82 includes 8x2.5" drivers delivering 150WRMS and the possibility of working in 16 Ω or 64 Ω. IP44 rated. Includes a versatile smart pan and tilt bracket made out of stainless-steel that permits adjusting the height at any point of the length of the column. White or black colour. Dimensions 83 x 648 x 87 mm / 3.27 x 25.51 x 3.43 in. (WxHxD). Weight 2.65 kg / 5.84 lb. Delivered by units. Price per unit.

860.00 Q2

High Performance Loudspeakers | NIMBO Series



NIMBO-14 (WH | BK)

2-way passive loudspeaker for surface mounting (1x 4" woofers and 1" tweeter). 40 WRMS @ 8 ohm. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. White or black color. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.

TBC Q2



NIMBO-14GD

2-way passive loudspeaker for surface mounting (1x 4" woofers and 1" tweeter). 40 WRMS @ 8 ohm. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Gold color. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.

TBC Q2



NIMBO-14CR

NIMBO-14 RAL customization. MOQ: 8 units. Delivery time: 45 days. Dimensions 250 x 148.7x 150 mm / 9.84 x 5.85 x 5.91 in. Weight 1.7 kg / 3.75 lb. Delivered by units. Price per unit.

TBC Q2



NIMBO-24 (WH | BK)

2-way passive loudspeaker for surface mounting (2x 4" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 80 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. White color. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.

530.00











NIMBO-24GD

2-way passive loudspeaker for surface mounting (2x 4" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 80 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Gold color. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.

530.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
 	<p>NIMBO-24CR NIMBO-24 RAL customization. MOQ: 8 units. Delivery time: 45 days. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.</p>	660.00
 	<p>NIMBO-26 (WH BK) 2-way passive loudspeaker for surface mounting (2x 6" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 140 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. White color. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.</p>	990.00 Q2
 	<p>NIMBO-26GD 2-way passive loudspeaker for surface mounting (2x 6" woofers and 1" tweeter). Capable of working at both 4 Ω and 16Ω in low impedance, featuring the front switch located behind the logo. 140 WRMS. Suitable for outdoor applications, with a wide dispersion pattern and IP-44 rating. Gold color. Dimensions 542,5 x 261 x 269 mm. / 21.35"x 10.27"x 10.59". Weight 8,5 kg. / 18.73 lb. Delivered by units. Price per unit.</p>	990.00 Q2
 	<p>NIMBO-26CR NIMBO-24 RAL customization. MOQ: 8 units. Delivery time: 45 days. Dimensions 370 x 180 x 180 mm. / 14.56"x7.08"x7.08". Weight 3 kg. / 6,61 lb. Delivered by units. Price per unit.</p>	1'200.00 Q2

High Performance Loudspeakers | ARQIS Series

ARQIS105i (WH | BK)

2-way (5,25" woofer and 1" HF tweeter) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 70 WRMS @ 8 Ω. 280W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. Double INPUT/STACK connector, Euroblock type, with security attachment screws, and metal safety sling included. 150°x130° dispersion pattern. Dimensions (WxHxD) 186 x 280 x 210 mm / 7,32 x 11,02 x 8,26 in. Weight: 3.6 kg



340.00

ARQIS106i (WH | BK)

2-way (6,5" woofer and 1" rotatable HF Compressor Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 120 WRMS@8Ω. 480W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. Double INPUT/STACK connector, Euroblock type, with security attachment screws, and metal safety sling included. 140°x160° dispersion pattern. Dimensions (WxHxD) 216x350x240mm / 8.50"x13.78"x9.45". Weight 7.4 kg / 16.31 lb



470.00

ARQIS108i (WH | BK)





2-way (8" woofer and 1" HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics, excellent sound quality and long term reliability, featuring 150 WRMS @ 8 Ω. 600W Peak power. Its smart wall bracket (included), allows for pan&tilt adjustment, employing a single screw for fastening. 130°x130° dispersion pattern. Dimensions (WxHxD) 244 x 390 x 280 mm / 9.60" x 15.35" x 11.02". Weight 8,4 kg / 18.52 lb



550.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	<p>ARQIS110i (WH BK)</p> <p>2-way (10" woofer and 1" rotatable HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics and long term reliability, featuring 300 WRMS @ 8 ohm. 1200W Peak power. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (110°x 110° dispersion pattern). Dimensions (WxHxD) 359x495x310mm / 14.13"x19.49"x13.86". Weight 14,8 kg</p>	<p>740.00</p>
	<p>ARQIS112i (WH BK)</p> <p>2-way (12" woofer and 1,4" rotatable HF Compression Driver) wooden loudspeaker cabinet with a compact format, stylish aesthetics and long term reliability, featuring 500 WRMS @ 8 Ω. 2000W Peak power. 35 mm mount socket and 8 x M10 rigging points, allowing for horizontal or vertical mounting options (120°x 110° dispersion pattern). Dimensions (WxHxD)416x565x352mm / 16.37"x22.24"x13.86". Weight 20,0 kg / 44.09 lb. Black color. Bracket not included. Optional ARQ112UB, TRIPO and SR12 accessories.</p>	<p>1'090.00</p>
	<p>ARQIS205i (WH BK)</p> <p>2-way (2x 5,25" woofer and 1" HF rotatable Compression Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 140 WRMS @ 8 Ω. 560W Peak power. Double INPUT/STACK connector, Euroblock + Speakon© type, 8 x M8 cabinet flying points, metal safety sling included. Its "U" shape wall bracket (included) allows for tilt adjustment. 150° x 40° dispersion pattern. Dimensions (WxHxD) 480x186x210mm / 18.89"x7.32"x8.26". Weight 8.4 kg. / 18.52 lb</p>	<p>550.00</p>
	<p>ARQIS208i (WH BK)</p> <p>2-way (2 x 8" woofer and 1" HF Compression Driver) wooden loudspeaker cabinet with a compact format and long term reliability, featuring 300 WRMS @ 8 Ω. 1200W Peak power. Double INPUT/STACK connector, Euroblock + Speakon© type, 8 x M8 cabinet flying points, metal safety sling included. Its "U" shape wall bracket (included) allows for tilt adjustment. 130°x30° dispersion pattern. Dimensions(WxHxD) 610x244x280mm / 24.01"x9.60"x11.02" . Weight 14.4 kg / 31.74 lb</p>	<p>850.00</p>

High Performance Loudspeakers | LABI Series



LABI1-C100i

LABI1-C100i is a versatile and discreet column loudspeaker, designed for indoor and outdoor fixed installations and portable applications. It features twelve 3" drivers with 0.75" neodymium voice coil each one, 300W AES. Its versatile profile allows the column to be installed in several ways such on the LABI subwoofers, on wall, pole, truss, etc. thanks to LABI1 accessories. Stand alone or combined with other LABI1-C100i and LABI1-SP18p to create a complete powerful plug & play solution. Dimensions: 89 x 1000 x 117 mm / 3.5" x 39.4" x 4.6". Weight: 7.8 kg / 17.2 lb

1'890.00

High Performance Loudspeakers | DROP Series



DROP6 (WH | BK)

ECLER DROP6 is a 2-way 6.5", 75W@8ohm pendant loudspeaker with a stylish design, including a 70/100V line transformer with 60/30/15 and 7,5W power selections, available at both high and low impedance levels. Dimensions (without accessories) Ø270mm x 355mm(H) / Ø10.6 in. x 14 in. (H). Weight 4.2 Kg / 9.26 lb. 2x stripped wire connection (5m).

420.00

High Performance Loudspeakers | OUTDOOR Series



ZEN-15 (GR | SD)

The new ZEN-15 in-ground loudspeaker with an elegant stone shape seamlessly blends the world of audio technology with the aesthetics of nature. Includes a 5,25" woofer and a 1" tweeter delivering 70W RMS @ 8ohm and 60W RMS @ 70/100V. Crafted to resemble a rugged, weathered stone, this discreet outdoor audio solution effortlessly integrates into outdoor environments, providing a harmonious balance between functionality and visual appeal. Granite or Sand color. Dimensions 410 x 260 x 289mm

TBC Q3



IG108

Weatherproof loudspeaker (IP65) with an omni-directional horizontal dispersion pattern (360°). 8" Kevlar woofer and 1" ACCW silk tweeter. 100 WRMS @ 8Ω, suitable for 70/100V (7.5/15/30/60 W @ 100V). Frequency response 50Hz to 23kHz. Security ground bracket included. It is ideal for music and message applications in outdoor areas. Dimensions 360 x 392.5 mm. Weight 8.5 kg

630.00

Commercial Loudspeakers | TRAIL Series



TRAIL103 (WH | BK)

3" lamp style loudspeaker cabinet, with high Impedance (15W and 30W taps) and Low Impedance (15 WRMS @4Ω) connections. Includes 3 different installation system accessories for ceiling light rails, surface mount and truss mount. Dimensions (without arm) Ø 96mm x 110mm. Weight 1kg White or black colour.

260.00


Commercial Loudspeakers | eAMBIT Series



EAMBIT103 (WH | BK)

Ultra compact 2-way (3.5" woofer and 0.5" tweeter) loudspeaker cabinet with neutral a discreet design, suitable for 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation. Dimensions (without accessories) 120 x 120 x 117 mm. Weight 1,275kg White or black color. **Delivered by master carton of 2 units. Price per unit.**

90.00



EAMBIT106 (WH | BK)

Ultra compact 2-way (6.5" woofer and 1" tweeter) loudspeaker cabinet with neutral an discreet design, suitable for 70/100V (5/7.5/15/30 W) and low impedance(50 WRMS @8Ω) audio lines. IP54 certified. Includes on-wall hardware, safety sling, screws and wrench for fast installation. Dimensions (without accessories) 210 x 210 x 160 mm. Weight 2,75kg White or black color. **Delivered by master carton of 2 units. Price per unit.**

145.00

Commercial Loudspeakers | AUDEO Series



AUDEO103 (WH | BK)

2-way loudspeaker cabinet. It features a 3.5" woofer and 0.5" tweeter. Suitable for high 70/100V (2.5/5/7.5/15 W) and low impedance (25 WRMS @8Ω) audio lines. Program power 50W. IP54 rated, protective front grill with anti-rust treatment, and accessories for wall-mounting included. Dimensions (without accessories) 132 x 134 x 110 mm. Weight 1,45kg White or black color. **Delivered by master carton of 2 units. Price per unit.**

160.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	<p>AUDEO106 (WH BK)</p> <p>2-way loudspeaker cabinet. It features a 6.5" woofer and 1" tweeter. Suitable for 70/100V (5/7.5/15/30 W) and low impedance (50 WRMS @8Ω) audio lines. Program power 100W. IP54 rated, protective front grill with anti-rust treatment, and accessories for wall-mounting included. Dimensions (without accessories) 242 x 242 x 163 mm Weight 2,3kg White or black color. Delivered by master carton of 2 units. Price per unit.</p>	<p>190.00</p>

Commercial Loudspeakers | eMOTUS Series

	<p>EMOTUS5PB-WH</p> <p>Stereo loudspeaker kit (2 x 25 WRMS @ 8Ω) including an active and a passive cabinet. eMOTUS5PBBK performs BT connection, balanced and unbalanced audio inputs. Includes an IR remote control and 0-10VDC remote port. Features: source selection, 2 band tone control, stereo/mono switch, auto stand-by and wall bracket and security steel cable. Dimensions 173x185x180mm. Weight 2.1 kg. White colour. Delivered by kit (active + passive loudspeakers). Price per kit.</p>	<p>440.00</p>
	<p>EMOTUS5P-WH</p> <p>Stereo loudspeaker kit (2 x 25 WRMS @ 8Ω) including an active and a passive cabinet and performing 2 audio inputs: balanced and unbalanced. Suitable for low impedance audio lines, includes source selection, 2 band tone control, stereo/mono switch, auto stand-by and wall bracket and security steel cable. Dimensions (without accessories) 173x185x180mm. Weight 2.1 kg White colour. Delivered by kit (active + passive loudspeakers). Price per kit.</p>	<p>340.00</p>
	<p>EMOTUS5OD (WH BK)</p> <p>5" woofer and 1" tweeter (40 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 100V (3,75/7,5/15/30W) and low impedance(8Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 173x181x180mm. Weight 2.4 kg White or black colour. Price per unit, sold in pairs.</p>	<p>190.00</p>
	<p>EMOTUS8OD (WH BK)</p> <p>8" woofer and 1" tweeter (100 WRMS @ 8Ω) loudspeaker cabinet ready for outdoor installation(IP65). Suitable for 70/100V (3,75/7,5/15/30W/60W) and low impedance(8Ω) audio lines. Includes a wall bracket and security steel cable. Dimensions (without accessories) 268x242x264mm. Weight 4.25 kg White colour. Price per unit, sold in pairs.</p>	<p>380.00</p>

Commercial Loudspeakers | SPHERES Series

	<p>EUC106 (WH BK)</p> <p>Spherical pendant loudspeaker featuring a 6,5" woofer, 0,5" tweeter. 40 WRMS @ 8Ω and 70/100V transformer.(32/ 16/ 8/ 4 W @ 100V). Dimensions (without accessories) ø270 x 215 (H). Weight 3 kg Stripped wire connection (3m). White or black colour.</p>	<p>190.00</p>
--	---	----------------------

Commercial Loudspeakers | HIGH EFFICIENCY Series

	<p>ECMP8</p> <p>150W high efficiency musical projector ready for outdoor applications due to its waterproof and sun screening building material (IP56). It performs an 8" LF driver and 1,4" HF coaxial driver, 150W @ 8Ω nominal power and 70/100V line transformer with 37, 5/75/150W/ 8Ω power options. Dimensions: WxHxD: 300 x 302 x 334mm /11.8" x 11.9" x 13.2". Weight: 11,0 kg / 24.3 lb</p>	<p>490.00</p>
--	--	----------------------

BILD

ARTIKEL | INFORMATION

UVP (CHF) | VI



ECMP12

300W high efficiency musical projector ready for outdoor applications due to its waterproof and sun screening building material (IP56). It performs an 12" LF driver and 1,7" HF coaxial driver, 300W @ 8Ω nominal power and 70/100V line transformer with 50/100/200W/8Ω power options. Dimensions: WxHxD: 407 x 410 x 378mm / 16.0" x 16.1" x 14.9". Weight: 20,0 kg / 44.1 lb

850.00

Subwoofers | KICK & EDGE Series



KICK-SB28

As the first Ecler outdoor subwoofer, the new KICK-SB28 features 2x8" woofers perfectly positioned to maximize the low frequency response while reducing the vibrations on the acoustic enclosure. It delivers 700 WRMS at 4Ω ready to be wall-mounted with the included bracket or positioned vertically and horizontally when needed. Dimensions (WxHxD) 660 x 450 x 250 mm / 255,98 x 17,71 x 9,84 in. Black colour.

TBC Q2



EDGE-SB110P

Breaking the limits of powerful bass sound in a compact size EDGE subwoofer is perfectly designed for small available spaces like underneath restaurant seats or wall-mounted in a corner with the included bracket. This powered subwoofer of 178 mm deep incorporates a 10" driver, 50Hz to 150Hz variable low pass filter, phase inverter and an amplified power output of 150W. Black color. Dimensions (WxHxD) 635 x 400 x 178 mm / 23,62 x 15,74 x 7 in.

TBC Q2

Subwoofers | ARQIS Series

ARQUISSB6Ti (WH | BK)



Wooden wall-mount subwoofer reinforcement cabinet, featuring a 6,5" driver and a passive 6,5" radiator. 480W peak power, 120 WRMS power @ 8 ohm and integrated 70/100V line transformer with 60 and 120W taps. Internal LPF with OFF, 120HZ and 150 HZ cut-off frequency selections. Installation U-bracket included. Dimensions (WxHxD) 250x390x130mm / 9.84"x15.35"x5.12". Weight 8,2 kg / 18.07 lb. White or black colour.

740.00

ARQUISSB10Ti (WH | BK)



Wooden wall-mount subwoofer reinforcement cabinet with a slim and compact format and long term reliability, featuring a 10" driver (150 WRMS @ 8 ohm, 600W peak power) and internal LPF (OFF/ 120Hz/150Hz). Euroblock connector, wall mount and 12 x M8 rigging points included. Dimensions (WxHxD) 600x442x228mm / 23.62"x17.40"x8.97". Weight 16,6 kg / 36.37 lb. White or black colour.


750.00

ARQUISSB12iBK




Wooden sub-woofer reinforcement cabinet with a compact format and long term reliability, featuring 300 WRMS @ 8 Ω and a 12" LF driver. 1200W Peak power. Double INPUT/STACK connector, Speakon© type. 8 x M8 rigging points included. Dimensions (WxHxD) 445 x 445 x 375 mm / 17.51 x 17.51 x 14.76 in. Weight 23 kg / 50,70 lb. Available only in black color.



990.00

BILD	ARTIKEL INFORMATION	
	<p>ARQUISSB15iBK</p> <p>Wooden sub-woofer reinforcement cabinet with a compact format and long term reliability, featuring 600 WRMS @ 8 Ω and a 15" LF driver. 2400W Peak power. Double INPUT/STACK connector, Speakon© type. 35 mm top-hat pole mount socket and 8 x M8 rigging points included. Dimensions (WxHxD) 534 x 525 x 460 mm / 21.02 x 20.67 x 18.11 in. Weight 32 kg / 70,54 lb. Available only in black color.</p>	<p>1'250.00</p>



Subwoofers | TRAIL Series

	<p>TRAILSB6TBK</p> <p>Wooden subwoofer reinforcement cabinet with a very compact format, featuring a 6,5" driver, 60 WRMS @ 8Ω, 70/100V line transformer (7.5/15/30/60 W), and internal Low Pass Filter(150Hz / OFF). Specifically designed to fulfil permanent installation requirements: concealed in false ceilings or partition walls, on walls' surface, etc. Installation accessories included. Dimensions 200x200x320 mm. Weight 6,3kg. Available only in black finish. Delivered by units. Price per unit.</p>	<p>520.00</p>
---	---	----------------------

Subwoofers | LABI Series

	<p>LABI-SB18</p> <p>LABI1-SB18 is an 18" passive subwoofer, 500W AES 8Ω, designed for fixed installations and portable applications (external amplification required). A stand alone compact subwoofer or combined with LABI1-C100i to create a complete powerful solution, easy to mount and plug and play. Dimensions: 513 x 513 x 704 mm / 20.2" x 20.2" x 27.7". Weight: 37kg / 81.8 lb.</p>	<p>2'250.00</p>
	<p>LABI-SB18P</p> <p>LABI1-SB18p is an 18" powered subwoofer, designed for fixed installations and portable applications. A stand alone compact subwoofer or combined with LABI1-C100i to create a complete solution. It performs 2400W Class D built-in amplification power: 1 x 1200W for its low frequency woofer, and 2x600W amplifiers, able to power up to 4 x LABI1-C100i. It also features DC protection to avoid damage to the loudspeakers, and performs 18 factory presets - selectable through the LCD screen. Dimensions: 513 x 513 x 704 mm / 20.2" x 20.2" x 27.7". Weight: 37kg / 81.8 lb.</p>	<p>4'790.00</p>

Industrial Loudspeakers | ROCK & COLUMN Series

	<p>ERK108</p> <p>Outdoor and cost-effective ground loudspeaker. It features a 8" woofer, 0.5" tweeter. 70/100V transformer (15W). IP65 rated. Ready to be installed in gardens, theme parks, leisure facilities, etc. Dimensions 325x290x270mm. Weight 5kg</p>	<p>200.00</p>
	<p>ECS803</p> <p>Column loudspeaker, featuring 8 x 3" woofer transducers, 100 WRMS @ 8Ω, low impedance direct connection and 70/100V transformer (Selector de potencia: 30/ 20/ 10/ 5 W 100V/ 8 Ω). Aluminium enclosure with included wall bracket and IP44 outdoor class. Dimensions (without accessories) 105x760x90mm. Weight 4.5 kg</p>	<p>240.00</p>

Industrial Loudspeakers | SOUND PROJECTOR Series

EPRS10TI



10 WRMS sound projector carefully selected for the most extended 70/100V paging and background music applications. Manufactured in reinforced ABS and IP55 rated, therefore suitable for outdoor superior performance in music high-quality applications. Power selection: 2,5/5/10W @ 100V. Dimensions Ø 138 x 205mm. Weight 1.6kg (including accessories).

90.00

EPRS20TI



20 WRMS sound projector carefully selected for the most extended 70/100V paging and background music applications. Manufactured in reinforced ABS and IP55 rated, therefore suitable for outdoor superior performance in music high-quality applications. Power selection: 5/ 10/ 20W @ 100V. Dimensions Ø 170 x 245mm. Weight 1.8 kg (including accessories).

115.00

EPHS30TI



30 WRMS horn loudspeaker carefully selected for the most extended 70/100V paging and background music applications, offering durability and optimal speech and music reproduction. Manufactured in reinforced ABS and IP66 rated, therefore suitable for outdoor superior performance. Power selection: 30W / 20W / 10W / 5W @ 100V. 30WRMS @ 8Ω. Dimensions Ø 246 x 292mm. Weight 2.4kg (including accessories).

150.00

EMSP50TI



50 WRMS 2-way musical horn carefully selected for the most extended 70/100V paging and background music applications, offering durability and optimal speech and music reproduction. Manufactured in reinforced ABS and IP66 rated, therefore suitable for outdoor superior performance in music high-quality applications. Power selection: 2.6/4.5/9/12.5/25/50W @ 100V. 50WRMS @ 8Ω. Dimensions 362x252x310mm. Weight 3.9kg (including accessories).

290.00

HIGH PERFORMANCE P.A. SETS | LABI Series

LABI1PACK1


- 2 x LABI1-SB18p
- 4 x LABI1-C100i
- 2 x LABI1-SAC
- 2 x LABI1-CAC
- 2 x LABI1-SPC
- 2 x LABI1-CFC
- 2 x LABI1-SWK



16'700.00

LABI1PACK2

- 1 x LABI1-SB18p
- 2 x LABI1-C100i
- 1 x LABI1-SAC
- 1 x LABI1-CAC
- 1 x LABI1-SPC
- 1 x LABI1-CFC
- 1 x LABI1-SWK



8'350.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD

ARTIKEL | INFORMATION

UVP (CHF) | VI

2 x LABI1-SB18p
4 x LABI1-C100i
2 x LABI1-SAC
2 x LABI1-CAC

LABI1PACK3



13'850.00

2 x LABI1-SB18p
2 x LABI1-C100i
2 x LABI1-SAC

LABI1PACK4



10'390.00

REMOTE CONTROLS & INTERFACES

Paging Stations



PAGENETDN

Desktop paging console for voice notices with Dante™ audio over IP. Features a 10" touch screen, a server client and a UCP server (User Control Panel). Since it's a server/UCP client device, it's possible to add other kind of control panels beside the ones destined for voice messages such as: volume control, sound source selection, presets recovery, communication via TCP/UDP with external devices, etc. Power over Ethernet or local power supply. Gooseneck microphone included

2'390.00



EMPAGE

Digital paging station (MPAGE16's evolution), compatible with HUB, MIMO88, MIMO88SG and MIMO1212SG digital matrixes. Includes: a gooseneck cardioid microphone (removable); 16 zone-selection keys; ALL, CLEAR and PAGE keys; 2 programmable keys, F1 & F2, for zone-group selection. Text labelling for destination areas by means of programmable electronic ink display. Dimensions (microphone excluded) 150mm x 180mm x 50mm. Weight 900g.

780.00



MPAGE1R

1-zone desktop paging station, compatible with any device including a phantom-powered microphone input (SAM series, COMPACT series, DAM614, MIMO88, CA series, HMA series, etc.). Internal connections for a secure wiring. Dimensions (microphone excluded) 120mm x 126mm x 43mm. Weight 625g.

280.00



MPAGE4

4-zone desktop paging station compatible with DAM614, CA series, etc. It allows for real-time paging with zones' destination selection. Selectable chime melody. Dimensions (microphone excluded) 120mm x 126mm x 43mm. Weight 650g.

430.00

Digital Controls & Panels



PULSO-4

PULSO-4 is a digital remote wall panel with an elegant minimalistic design. Featuring aluminum frame and capacitive 4" TFT 480x480 display, the new PULSO wall panels are the perfect choice to load the User Control Panels of VIDA Series, EclerNet and HUB Series. Single unit EU electrical wall box. PoE or external power supply.

TBC Q3

BILD



ARTIKEL | INFORMATION

PULSO-6

PULSO-6 is a digital remote wall panel with an elegant minimalistic design. Featuring aluminum frame and capacitive 5,5" TFT 720x1280 display, the new PULSO wall panels are the perfect choice to load the User Control Panels of VIDA Series, EclerNet and HUB Series. Single unit EU electrical wall box. PoE or external power supply.

TBC Q3

PULSO-10

PULSO-10 is a digital remote wall panel with an elegant minimalistic design. Featuring aluminum frame and capacitive 10" TFT 1280x 1800 display, the new PULSO wall panels are the perfect choice to load the User Control Panels of VIDA Series, EclerNet and HUB Series. Single unit EU electrical wall box. PoE or external power supply.

TBC Q3

WPNETTOUCH

Remote control TFT touchscreen compatible with all EclerNet products such as: MIMO4040DN, MIMO88/SG, MIMO1212SG, NXA Series and DUO-NET PLAYER. Incorporates a capacitive 10" touch screen, a server client and UCP server (User Control Panel). When including a WPNETTOUCH in an EclerNet installation is not necessary to use a computer to manage connected devices, neither to have the UCP panels created for the project. Power over Ethernet or local power supply. Surface-mount accessories included. Compatible with VESA75 mounting standard. 260x178x28mm, 700gr.

1'290.00

WP22DN

Dante™ interface in a wall panel format. It features 2 audio MIC/LINE Combo connector inputs in its frontal panel and 2 Dante™ conversion channels either directly or by the sum of channels (stereo to mono conversion). Also, it features 2 analogue outputs with duplicated connectors in XLR format for the front panel and Euroblock on the rear panel, both linked to 2 Dante™ channels coming from the local network. PoE supply or local power supply.

890.00

WPNETEX

EclerNet compatible digital wall panel, including an LCD screen, a digital rotary control (encoder) and four selection keys, all of them programmable to perform extended control functions: selection of sources or presets + volume adjustment, event triggering, adjustment of equalizer tones, etc. Ethernet connection interface. PoE power or by local power supply.

890.00 EOL

WPNET4KV

EclerNet compatible wall panel. It features a LCD screen, encoder and 4 selection keys. Works perfectly to enable volume control, source and preset selection functions. Ethernet interface. PoE or local power supply.

490.00

WPNET8K

EclerNet compatible wall panel. It features a LCD screen and 8 selection keys. Works perfectly to enable presets or source selection functions. Ethernet interface. PoE or local power supply.

490.00

BILD

ARTIKEL | INFORMATION

UVP (CHF) | VI


EMCONTROL1

Digital control panel for the HUB matrix with a wall format, It makes it possible to act as a zone control, enabling the user to have 3 functions : volumen adjustment/MUTE, selection of musical sources and EQ adjustment with 3 band tone control. Coupled to a WPa type panel with an audio connector, provide remote control + balanced audio signal to the HUB, using only a single CAT5 type cable or higher. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.

280.00
Analogue Controls & Panels | WPA Series

WPABT

Class 1 bluetooth receiver (range 25m) A2DP profile, which keeps the standard wall-panel format of the WPa series. Include a Euroblock balanced stereo output, double-mono configurable. Easy device name, PIN, stereo / mono output configuration using the Ecler Bluetooth® Manager application for Windows devices. GPO available, useful for automatic priority management. Surface installation box included. Dimensions 86 x 38 x 86 mm.

290.00

WPAMIX-T

2 channel micro-mixer which keeps the standard wall-panel format of the WPa series. It allows to mix a stereo unbalanced signal (2xRCA) with a microphone signal (XLR), getting a balanced mono output that can be sent to a preamplifier, amplifier, mixer, digital or analogue matrix, etc. The MIC input includes a 2 band EQ (BASS, TREBLE) and talk-over function. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.

190.00

WPAVOL

Remote wall panel control for one volume management. Compatible with all Ecler 0-10V DC REMOTE control port, like ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.

100.00

WPAVOLJ

Remote wall panel control for one volume management and a front panel stereo mini-jack connector. Compatible with all ECLER 0-10V DC REMOTE control port, like MPA-R, ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc.

105.00

WPAVOLSR

Remote wall panel control for one volume management + source or preset selection. Compatible with all Ecler 0-10V DC REMOTE control port, like MPA-R, ALMA, MIMO88 / SG, NXA series, CA series, GPA series, etc. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.

125.00

WPAVOLSRJ

Same features as WPAVOL-SR + front panel stereo mini-jack connector. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.

145.00





WPACNX-CBO

Connection wall plate with Female 3 pin XLR connector + Jack ST (combo connector). Screw-type connector at the back (no solder needed). Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.






99.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	WPACNX-JRCA Connection wall plate with 1 x stereo minijack and 2 x RCA connectors. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	95.00
	WPAHAT6 70 / 100V line attenuator with integrated 24 VDC priority relay. 6W maximum output power. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	108.00
	WPAHAT40 70 / 100V line attenuator with integrated 24 VDC priority relay. 40W maximum output power. Universal surface-mount installation box included. Dimensions 86 x 38 x 86 mm.	130.00
	WPAHAT100 70 / 100V line attenuator with integrated 24 VDC priority relay. 100W maximum output power. Universal surface-mount installation box included. Dimensions 172 x 38 x 86 mm.	145.00

ACCESSORIES
Product Accessories

	ETH232AD Ecler ETH232AD is a serial interface that allows bidirectional transparent transmission between RS-232/422/485 and Ethernet. It includes a setting webpage for Ethernet and Serial customized settings. Dimensions: 100 x 86 x 26 mm (3.94" x 3.39" x 1.02") Weight: 0.5kg / 1.10 lb.	270.00
	1UHRMKIT Kit that enables a half-width x 1U height rack device to be mounted into a standard width rack cabinet	36.00
	2UHRMKIT Kit that enables a half-width x 2U height rack device to be mounted into a standard width rack cabinet.	49.00
	VEORACK19 Universal 19" rack mount accessory. Mounting screws and Velcro® included.	116.00
	PUM3 Ecler PUM3 is a rack-mount accessory that allows to mount two half-width RU devices in 1 standard width RU space. Mounting screws included.	20.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	WPA2FMBOX Double Flush-Mount box, compatible with the WPa wall panel series. It includes a single frame for fitting 2 adjacent panels in a twin housing.	60.00
	WPA2SMBOX Double Surface-mount box, compatible with the WPa wall panel series. It includes a single frame for fitting 2 adjacent panels in a twin housing.	65.00
	WPPSU External, universal AC/DC converter for the DC supply of remote panels and devices. Compatible with all the WPa series panels requiring external DC power supply	80.00 EOL
	WP24PSU Ecler WP24-PSU is a 24VDC 0.5A external PSU. International AC plugs set. Coaxial connector (+ center), compatible with eMPAGE, DN44BOB, WPNET Series, eMCONTROL1, WPaMIX-T and WPaBT.	58.00
	LABI1-SWK Subwoofer-Wheel-Kit. 4 wheel kit for LABI1-SB18/18p subwoofer	195.00
	LABI1-SWK Column-Flight-Case. Flight case for 2 LABI1-C100i + wiring + mounting accessories	1'190.00
	LABI1-SPC Subwoofer-Protection-Cover. Nylon protection cover for LABI1-SB18/18p subwoofer	240.00

Audio Cables


CNXE BEB1	Euroblock 3 pin to Euroblock 3 pin premade cable, 1 metre length.	24.00
------------------	---	--------------







CNXE BEB2M5	Euroblock 3 pin to Euroblock 3 pin premade cable, 2.5 metre length.	25.00
--------------------	---	--------------








CNXE BLINK4	Euroblock 3 pin to Euroblock 3 pin, 4 connectors premade link cable (amplifiers, preamps and mixers inputs link wire, to share the same audio signal).	24.00
--------------------	--	--------------

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info










BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	CNXEBCA1 Double Euroblock 3 pin to double RCA male and female connection premade cable including RCA to Euroblock unbalancing, 1 metre length.	28.00
	CNXRCAEBAD Euroblock 3 pin to RCA MONO female adapter including RCA to Euroblock unbalancing.	23.00
	CNXMJXLR2 2m length minijack ST to mono XLR male. Includes an internal resistance for overload protection and a proper sum of the signals.	28.00
	CNXXLRFEB Euroblock 3 pin to XLR female connection premade cable, 0.5 metre length.	19.00

Loudspeakers Hardware

	RAILAPTOR (WH BK) RAILAPTOR is an adapter for hanging compatible loudspeakers from a ceiling light rail. It is suitable for eMOTUS50D, AUDEO103 and AUDEO106 cabinets and light rails performing 4 wire 3 circuit track system such as Global Track Pro, Eutrac or other compatible systems. Dimensions: 85x150x30 mm / 3.3"x5.9"x1.2". Weight: 130gr / 0,29lb. White or black colour.	29.00
	ARQ108UB (WH BK) Optional U-BRACKET accessory kit available for the ARQIS108i model. White or black colour.	70.00
	ARQ110UB (WH BK) Optional U-BRACKET accessory kit available for the ARQIS110i model. White or black colour.	80.00
	ARQ112UB (WH BK) Optional U-BRACKET accessory kit available for the ARQIS112i model. White or black colour.	85.00
	AVICCAN6L Low Profile Back Can for VIC6 in-ceiling loudspeakers. Delivered by master carton of 2 units. Price per unit.	48.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	AVICCAN8L Low Profile Back Can for VIC8 in-ceiling loudspeakers. Delivered by master carton of 2 units. Price per unit.	56.00
	AVICSG Printable squared grill for VIC series (6 & 8 inches compatible). Magnetic fixation. White colour. Delivered by master carton of 2 units. Price per pair.	50.00
	AVICRG6 (WH BK) Printable round grill for VIC series (6 inches compatible). Magnetic fixation. White or black colour. Delivered by master carton of 2 units. Price per pair.	45.00
	AVICRG8 (WH BK) Printable round grill for VIC series (8 inches compatible). Magnetic fixation. White or black colour. Delivered by master carton of 2 units. Price per pair.	50.00
	ICTB6 Tile bridge compatible with IC6 in-ceiling loudspeakers. Sold in kits of 2 units. Price per kit.	90.00
	ICTB8 Tile bridge compatible with IC8 and IC6CLASS series in-ceiling loudspeakers. Sold in kits of 2 units. Price per kit.	99.00
	MSTANDAUDEO Adaptor which allows to mount an AUDEO103/AUDEO106/eMOTUS5/CUBE loudspeaker on a standard microphone stand. (microphone stand not included)	45.00 EOL
	COLORPAINT Launching of painting in ceiling loudspeakers grilles (PKIC6, PKIC8, AVICSG, AVICRG) in a RAL colour . There is no charge for launching when painting a minimum of 100 units in the same RAL colour.	280.00
PAINT1S	Painting by unit when there are less than 10 units.	47.00
PAINT10S	Painting by unit when there are more than 10 units and with a maximum of 99 units.	25.00
PAINT100S	Painting by unit when there are 100 or more units.	17.00
	PKIC6 Accessory for personalizing the IC6 ceiling loudspeaker. The kit includes a grille that can be painted (with the appearance of the IC6CLASS) and an accessory (anchor ring) to mount this grille on the IC6. Easy to paint and mount.	45.00

Preisliste gültig ab 4. April 2024

VI = Verfügbarkeits-Info

BILD	ARTIKEL INFORMATION	UVP (CHF) VI
	PKIC8 Accessory to personalize the IC8 ceiling loudspeaker. The kit includes a grille that can be painted (with the appearance of the IC6CLASS) and an accessory (anchor ring) to mount this grill on the IC8. Easy to paint and mount.	45.00
	POLE01 Adjustable 35 mm rod for pole for loudspeaker mount on top of a sub-woofer unit (ARQIS110i on top of ARQISSB15).	50.00
	SR12 Mount bracket for ARQIS110i and ARQIS112i loudspeakers. Delivered by master carton of 2 units. Price per unit.	49.00
	LABI1-SAC Subwoofer-adapter-column, to install the LABI1-C100i satellite loudspeaker on LABI1-SB18p	220.00
	LABI1-CAC Column-adapter-column, to connect vertically two LABI1-C100i column loudspeakers. Includes 60cm Speakon®-Speakon® cable. Warning: Only for stacking, NOT for flying	260.00
	LABI1-TBC Truss-Bracket-Column. Support to install a LABI1-C100i loudspeaker to truss	160.00
	LABI1-PBC Pole-Bracket-Column. Pole adaptor to install LABI1-C100i loudspeakers in a 35mm standard pole	270.00
	LABI1-WBC Wall-Bracket-Column. LABI1-C100i wall mount bracket	180.00
	LABI1-HBC Horizontal-Bracket-Column. High-density foam pieces to let LABI1-C100i rest on the floor horizontally. Allows 0°/ 30°/ 45° inclinations relative to the horizontal surface	45.00
	LABI1-ODCNX Outdoor kit to cover LABI1-C100i connections and make it ready for outdoor applications	90.00